



INDUSTRIAL CONSTRUCTION COATINGS

Silver Bullet Fusion – SBF 7000

MTD Sheet

Product Benefits:

- Easy application and installation
- Direct to metal applications no primer required.
- Rust inhibitors included superior corrosion resistant.
- Brush, roller, or airless applications
- Eco Friendly, lead free, formaldehyde free, No Voc.
- Non flammable
- Easy to clean.
- Interior exterior use.
- High UV stability
- 15 colours to choose from
- 100% watertight.
- Extremely high solid content allowing single coat applications were valid.
- Potable

Uses and Applications:

- For installations onto IBR and Chromadek sheeting.
- General steel structures.
- Rusted surfaces that needs rehabilitation.
- Completely rehabilitate deteriorated gutters.
- Fibre cement and Cement roof tiles.
- Concrete dams.
- Steel tanks, water tanks.
- Prevents rust when installed properly.



www.industrialconstructioncoatings.co.za

sales@industrialconstructioncoatings.co.za | 073-209-3251

290 Foal Road, Knoppieslaagte, Centurion, 0035



INDUSTRIAL CONSTRUCTION COATINGS

Surface Preparation:

- New steel structures must be clean, dry, and free from contamination prior to painting. Oil and grease should be removed completely with a quality degreaser and rinsed with clean water. Observe a water break-free surface during rinsing.
- Areas of rust should be cleaned, and wire brushed or sandblasted to a clean surface. Before application of SBF 7000. Rust that has been removed should be bagged and discarded so that no rust can spread.
- Other structures should be clean and dry free from any oil, or foreign matter.

General Data:

Spread Rate	Approximately 8m ² per litre at 125 micron, wet film thickness. On a two-coat application, 160m ² p/drum excluding wastage.
Drying Time:	At 25°C on average 36 minutes
Colours:	15
Overcoating Times:	4 hours at 25°C
Emulsion Type:	Adhesion promoted acryl hybrid quad cell technology
Gloss Level:	Medium Sheen
Solids by Volume:	38%
TVOC:	3.45 g/l

Precautions:

- Clean up unwanted spills IMMEDIATELY with lots of water.
- Do not paint when temperature approaches 10°C or drops below.
- Overcoating time will be extended in cold weather or wet weather.
- Before using on aluminium prepare a piece and test first.
- Ventilate well when using in confined spaces and take regular breaks.
- When ingested, induce vomiting (if conscious). Give patient plenty of water and seek medical advice Immediately.
- **Eye Contact:** Rinse well with cold water and seek medical advice.
- **Skin Contact:** Remove contaminated clothing and wash and rinse skin properly.
- If skin is irritated seek medical advice.



www.industrialconstructioncoatings.co.za

sales@industrialconstructioncoatings.co.za | 073-209-3251

290 Foal Road, Knoppieslaagte, Centurion, 0035